

UTILITY APPLIANCES



SIMPLIFY MAINTENANCE IN THE FIELD

Thunder Creek's versatile utility appliances simplify maintenance and reduce the downtime that comes with servicing off-road machinery. These powerhouses can function as stand-alone units from the bed of a pickup or they can be installed in the rear utility box of any new Thunder Creek fuel and service trailer.

AIR COMPRESSOR

35 CFM at 100 PSI

COMPRESSOR + GENERATOR

17.2 CFM at 100 PSI 3500 Watts

WELDER + COMPRESSOR + GENERATOR

20 CFM at 100 PSI 5000 Watts 40A - 190A Variable Operating Range

UTILITY APPLIANCES FOR YOUR TRAILER OR TRUCK



FUEL | DEF | SERVICE | LUBE



UTILITY APPLIANCES

FITS INSIDE A REAR UTILITY BOX ON YOUR FUEL TRAILER OR IN YOUR TRUCK BED



AIR COMPRESSORS 45" W x 22" D x 36" H | 320 lbs.



COMPRESSOR + GENERATOR 45" W x 22" D x 36" H | 360 lbs.



WELDER + COMPRESSOR + GENERATOR 51" W x 21" D x 30" H | 375 lbs.

COMPRESSOR	 35 CFM @ 100 PSI Two Stage Compressor Splash Lubricated Cast Iron Crankcase Cast Iron Head Large Canister Intake Filter Stainless Steel Braided Discharge Hose 8 Gallons of Air Tank Storage 	 17.2 CFM @ 100 PSI Two Stage Compressor Splash Lubricated Cast Iron Crankcase Cast Iron Head Large Canister Intake Filter Stainless Steel Braided Discharge Hose 8 Gallons of Air Tank Storage 	 20 CFM at 100 PSI 10 Gallons of Air Tank Storage Built in Unloader
GENERATOR	N/A	 Industrial 3500 W Generator Four NEMA 5 - 15R Receptacles, 230V Outlet Brushless Alternator Total Harmonic Distortion less than 5% 100% Copper Windings 	 Capacitor Style Generator 5000 Watts of Max. AC Output 4200 Watts of Rated AC Output 230V Twist Lock Connections (qty 1) 110V Outlets (qty 2)
WELDER	N/A	N/A	 40A-190A Variable Operating Range 150A at 100% Duty Cycle Patented 20' Weld Leads Included Amperage Adjustment and Maximum Amperage Boost on Electrode Holder
ENGINE	 389 CC Honda GX390 Gasoline Engine with Electric Start Battery included when installed in a Thunder Creek Trailer 	 420 CC Rato Gasoline Engine with Electric Start Battery included when installed in a Thunder Creek Trailer 	 429 CC Kohler Gasoline Engine with Electric Start 3,600 RPM Drive System: Self Cooling, Tensioning and Cleaning Poly-Link Belt Auto Throttle Control Battery included when installed in a Thunder Creek Trailer
DESIGN FEATURES	 3/16" Base Plate to Reduce Vibration 14 ga. Powder Coated Two-Piece Belt Guard Belt tightening system pulls engine straight to ensure constant belt alignment. Regulator and two gauges for tank and outlet pressure. 16.5" fly wheel for extra cooling and longer life Manual drain valves for proper maintenance. Quality pilot valve unloader. 	 3/16" Base Plate to Reduce Vibration 14 ga. Powder Coated Two-Piece Belt Guard Belt tightening system pulls engine straight to ensure constant belt alignment. Regulator and two gauges for tank and outlet pressure. 16.5" fly wheel for extra cooling and longer life Manual drain valves for proper maintenance. Quality pilot valve unloader. 	 All three functions can operate simultaneously. Electrode holder has built-in amperage adjustment knob and the ability to bypass to deliver maximum amperage with boost control button. Powder coated twin tanks with saddle bracket base. Cast iron air pump has 3 cylinder head design. Automatic throttle control on engine for Compressor and Welder. True 2 generator system allows safe simultaneous use of welder and generator. Integrated cold weather engine provision. Battery box included.
REEL	When installed in a rear utility box: • 50' x 1/2" Air Hose Reel	When installed in a rear utility box:50' Combination 3/8" Air Hose and Electric Cord Reel	When installed in a rear utility box:50' Combination 3/8" Air Hose and Electric Cord Reel

>> QUESTIONS? CONTACT: Glen (Scooter) Barney | 801-978-1620 | glbarney@wheelercat.com